

## **HDMI 2.0**





### BHH (version 2.0)

- Enables transmission of High Dynamic Range (HDR) video
- Bandwidth up to 18Gbps
- 4K@50/60 (2160p), which is 4 times the clarity of 1080p/60 video resolution
- HDCP 2.2
- Up to 32 audio channels for a multi-dimensional immersive audio experience
- Up to 1536kHz audio sample frequency for the highest audio fidelity
- Simultaneous delivery of dual video streams to multiple users on the same screen
- Simultaneous delivery of multi-stream audio to multiple users (Up to 4)
- Support for the wide angle theatrical 21:9 video aspect ratio











### CHH (version 2.0)

- Enables transmission of High Dynamic Range (HDR) video
- Bandwidth up to 18Gbps
- 4K@50/60 (2160p), which is 4 times the clarity of 1080p/60 video resolution
- HDCP 2.2
- Up to 32 audio channels for a multi-dimensional immersive audio experience
- Up to 1536kHz audio sample frequency for the highest audio fidelity
- Simultaneous delivery of dual video streams to multiple users on the same screen
- Simultaneous delivery of multi-stream audio to multiple users (Up to 4)
- Support for the wide angle theatrical 21:9 video aspect ratio













# **HDMI 2.1**







- Certified Version 2.1 HDMI Cables
- Dynamic (HDR) video
- Support 48Gbps ultra high bandwidth
- Support 8K@60Hz ,4K@120Hz
- HDCP 2.2
- Support Ethernet function
- Support eARC













- Certified Version 2.1 HDMI Cables
- Dynamic (HDR) video
- Support 48Gbps ultra high bandwidth
- Support 8K@60Hz ,4K@120Hz
- HDCP 2.2
- Support Ethernet function
- Support eARC















# **TOSLINK**







#### **BFO**

- 24K Gold plated connectors
- Precision crafted Toslink heads
- Insulated core
- 6mm OD cable

### **BMFO**

- Precision crafted metal heads
- Precision crafted fiber
- 24k Gold plated tip
- 6mm OD cable





#### **CFO**

- Precision crafted heads
- Precision crafted fiber
- 24k Gold plated tip
- 2.2mm OD cable

# 3.5MM





### **BMM**

- •• 24k Gold plated connectors
- 99.99% oxygen free copper conductors
- Easy-flex and durable PVC jacket
- Precision crafted metal heads

### **BYF**

- 24K Gold plated connectors
- Precision crafted heads
- EMI/RFI Shielding





# **RCA**





### **BSA**

- 24K Gold plated connectors
- 99.99% oxygen free copper conductors
- EMI/RFI Shield
- Easy-flex and durable PVC jacket
- Precision crafted metal heads

### **BMSW**

- 24K Gold plated connectors
- 99.99% oxygen free copper conductors
- EMI/RFI Shield
- Easy-flex and durable PVC jacket
- · Precision crafted metal heads





# **Y ADAPTORS**





#### **BYA**

- 24k Gold plated connectors
- 99.99% oxygen free copper conductors
- EMI/RFI shielded
- Easy-flex and durable PVC jacket
- · Precision crafted metal heads

#### **BMYC**

- 24k Gold plated connectors
- 99.99% oxygen free copper conductors
- EMI/RFI shielded
- Easy-flex and durable PVC jacket
- Precision crafted metal heads





#### **BMYG**

- 24k Gold plated connectors
- 99.99% oxygen free copper conductors
- EMI/RFI shielded
- Easy-flex and durable PVC jacket
- Precision crafted metal heads



# RG6

### RG6

- RG6 coaxial cable
- 'F' terminated for indoor/outdoor use with satellite, antenna and cable equipment
  Rated up to 2300 Mhz
- UL listed









### MBP4

- 4 piece banana plug set
- · 24K gold plated
- Side barrel, fastening screws
- Black/Red barrel sheaths
- Supports 7 AWG wire

### **MCK200**

- Residue-Free
- Alcohol and Ammonia free
- Anti-Drip
- Microfiber Antistcatic Cleaning Cloth included
- 200ml easy spray bottle



Residue-Free



Alcohol and Ammonia free







Microfiber Antistcatic Cleaning Cloth included

# **Conduit**

## **MAESTRO**

### MCM<sub>2</sub>



2 X 30" CONDUIT 15 mm X 25 mm 5/8" X 1"

2 X 9" CONDUIT 15 mm X 25 mm 5/8" X 1"



**Inside Corner** 



**Outside Corner** 



1x

T-Bracket



900

1x



Coupler



Two Sided Tape



**Paintable** 



Fits 3 to 4 Cables

### MCM4



**Inside Corner** 

1x

4x



**Outside Corner** 

Coupler




T-Bracket



4 X 30" CONDUIT 15 mm X 25 mm 5/8" X 1"

4 X 9" CONDUIT 15 mm X 25 mm 5/8" X 1"



3х

Two Sided Tape





Fits 3 to 4 Cables

Page 9

# Switcher/Splitters





#### MH2-12

- 1 HDMI input 2 HDMI outputs
- HDMI version 2.0, 4K UHD
- Input & output cable lengths: up to 15m each
- HDCP2.2 complient
- AC adaptor included

Specification:
4K x 2K@60HZ (2160P)
HDMI v2.0a, HDCPv2.2
18Gbps Max bandwidth
Supports LPCM 7.1 CH Dolby Digital plus, and DTS-HD True audio
24k gold-plated connectors
Input cable max length: 15 meters
Output cable max length: 15 meters each
EDID configurable











#### MH2-31

- 3 INPUT TO 1 OUTPUT 4K2K HDMI 2.0 SWITCHER
- 4K x 2K@60HZ (2160P)
- HDMI v2.0a, HDCPv2.2
- 18Gbps Max bandwidth
- Supports LPCM 7.1 CH Dolby Digital plus, and DTS-HD True audio
- 24k gold-plated connectors
- Input cable max length: 8 meters
- Output cable max length: 10 meters each
- Power adaptor and remote included





# **Audio Converter**





#### MAE-MC1

- Toslink or coaxial digital audio inputs
- Sampling rate 32, 44.1, 48 and 96 KHz
- RCA left/right analogue outputs
- Digital to analogue audio
- AC adaptor included

#### MAS1X3

- Input Audio: 1 X Toslink digital audio
- Output Audio : 3X Toslink digital audio
- Maximum Output Cable Length: 40 meters
- Supports Audio streaming Dolby AC-3, Dolby 5.1, Dolby Digital, DTS and LPCM2.0
- Sampling rate: 32, 44.1, 48 and 96 KHz
- Over-voltage protection
- Only the USB power cable included





# **Phone Preamp**





### **MPA2033**

 Converts low-level stereo phono signal from a turntable into a high-level line signal going into an amplifier's auxiliary input





# BT SENDER / RECEIVER MAESTRO





### **BTI-029**

- One button for easy plug and play operation
- Bluetooth V5.0 transmitter/receiver
- AptX Low Latency technology
- Supports two concurrently connected devices and automatic pairing
- Rechargeable battery provides 12 to 15 hours of portable operating time. The BTI-029 may also be used continuously while plugged in
- Includes both optical and 3.5mm inputs and outputs
- Three audio Cables include:
- 1 x 3.5 mm to 3.5 mm male
- 1 x 3.5 mm female to two RCA male
- 1 x TOSLINK optical cable
- Micro USB input connection port for charging (Wire included)







Bluetooth V5.0

10 Meters Range

AptX Technology

#### SK-I3

- One button for easy plug and play operation
- · Bluetooth V5.0 transmitter/receiver
- AptX Low Latency technology
- · Supports two concurrently connected devices and automatic pairing
- Includes both optical and 3.5mm inputs and outputs
- Three audio Cables include:
  - 1 x 3.5 mm to 3.5 mm male
  - 1 x 3.5 mm female to two RCA male
  - 1 x TOSLINK optical cable
- · Micro USB input connection port for charging (Wire included)







AptX Technology



# **POWER BARS**





#### MPB6

- 6 outlets (5 regular + 1 adaptor)
- 1080 joules
- 4' power cord with space saving 90° plug
- X3 MOV (Metal Oxide Varistor) technology
- Safety shutdown technology
- Power ON/OFF/RESET switch
- Surge protection and ground status LED

### MPB8

- 8 outlets (5 regular + 3 adaptors) with childproof slide covers
- 2160 joules
- 8' power cord with space saving 90° plug
- 40 dB EMI/RFI noise filter
- X3 MOV (Metal Oxide Varistor) technology
- Safety shutdown technology
- Power ON/OFF switch
- Surge protection and ground status LED



# **POWER BARS**





#### M<sub>6</sub>P

- 6 outlet Power Surge Block
- Electrical Rating: 15A, 120V, 60Hz, 1800W
- Surge Protection (1080J)
- LED Indicator for Surge Protection
- 2-in-1 Power & Circuit Breaker Rocker Switch
- 4ft Cord, 90 Degree Plug

#### MP4U

- 4 outlet Power Surge Block
- Electrical Rating: 15A, 120V, 60Hz, 1800W
- Surge Protection (1080J)
- LED Indicator for Surge Protection
- 2-in-1 Power & Circuit Breaker Rocker Switch
- Each USB-A output up to 5V/2.4A
- 4ft Cord, 90 Degree Plug



• 2 USB-A output 5V/2.4A



# **POWER BARS**





#### MP8U

- 8 outlet Power Surge Block (20W Power Delivery Fast Charging)
- Charges compatible devices up to 3x faster
- Electrical Rating: 15A, 120V, 60Hz, 1800W
- Surge Protection (2160J)
- LED Indicator for Surge Protection
- 2-in-1 Power & Circuit Breaker Rocker Switch
- 2 USB-A & 1 USB-C Chargers
- USB-C in Use Only: 5V/3A, 9V/2.22A, 12V/1.67A Up to 20W PD Max.
- USB-A Both in Use: 5V/3A, Total: 15W Max.
- 6ft Cord, 90 Degree Plug



• 2 USB-A output 5V/3A 15w MAX



• 1 USB-C output 5V/3A, 9V/2.22A, 12V/1.67A Up to 20W PD Max

